

MATERIAL SAFETY DATA SHEET

AQUA 500

1.0 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER/SUPPLIER:

Chem and Lube
1901 South 12th Street
Allentown, PA 18103-4777

Emergency Spill Information:

1-800-255-3924 Chem-Tel (USA)

Other Product Information:

610-798-9222

2.0 COMPOSITION/INFORMATION ON INGREDIENTS

Component

Chemical Name: Petroleum Hydrocarbon plus Additives.

3.0 HAZARDS IDENTIFICATION

Toxic and Hazardous Ingredients: None

Permissible Concentrations (air): N/A

Chronic Effects of Overexposure: None when used with good personal hygiene practices. May otherwise cause skin and eye irritation upon prolonged or repeated contact.

Acute Toxicological Properties: No Data Available.

Potential Health Effects:

Eye Contact: Avoid eye contact.

Skin Contact: Prolonged or repeated contact may cause skin irritation.

Inhalation: Remove exposed person to fresh air if discomfort is experienced while handling hot product.

Ingestion: Do not take internally. Contact a physician immediately.

HMIS Code: (Health: 0) (Flammability: 1) (Reactivity: 0)

NFPA: (Health: 0) (Flammability: 1) (Reactivity: 0)

ADVICE TO PHYSICIANS: High velocity injection under the skin may result in serious injury. If left untreated the affected area is subject to infection, disfigurement, lack of blood circulation and may require amputation. When dispensed by high pressure equipment this material can easily penetrate the skin and leave a bloodless puncture wound. Material injected into a finger can be deposited into the palm of the hand. Within 24-48 hours the patient may experience swelling, discoloration, and throbbing pain in the affected area. Immediate treatment by a surgical specialist is recommended.

4.0 FIRST AID MEASURES

Eye: Flush eyes with plenty of water and get medical attention.

Skin: Wash exposed skin with soap and water. Get medical attention if irritation develops.

Inhalation: If adverse effects occur, remove to uncontaminated area. Get medical attention.

Ingestion: If a large amount is swallowed, get medical attention immediately. Do not induce vomiting.

5.0 FIRE FIGHTING MEASURES

Flashpoint: 363° F **Method:** C.O.C.
UEL: Not determined **LEL:** Not determined
Autoignition Temperature: Not determined.
Flammability Classification: Not flammable.
Extinguishing Media: Dry chemical or waterfog or CO2 or foam or sand/earth. Water may cause frothing. Closed containers may be cooled with water.
Unusual Fire and Explosion Hazards: Dense smoke.
Fire Fighting Equipment: Firefighters should wear an approved self-contained breathing apparatus. Do not use water except as fog.

6.0 ACCIDENTAL RELEASE MEASURES

Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand or vermiculite. Sweep up and dispose as solid waste in accordance with local, state and federal regulations.
Waste Disposal: Dispose of in accordance with all applicable local, state and federal regulations.

7.0 HANDLING AND STORAGE

Handling: No special requirements if handled with reasonable care.
Storage: Do not store in high temperature areas or where subject to open flames. Keep container closed until ready for use.

8.0 CHEMICAL AND PHYSICAL PROPERTIES

| | |
|---------------------|--|
| Appearance and Odor | : Amber (semi-solid), mineral oil odor |
| pH | : N/A |
| Vapor Pressure | : Negligible @ 20° C(mm Hg) |
| Vapor Density | : N/A |
| Boiling Point | : N/A |
| Melting Point | : N/A |
| Solubility | : Negligible @ 25°C |
| Specific Gravity | : 0.972 @ Room Temperature (water = 1) |
| Volatility | : N/A |
| Evaporation Rate | : N/A |

9.0 SPECIAL PERSONAL PROTECTION

Eye: Chemical safety goggles and, if handled hot, full face shield.

Skin: Wear protective gloves if prolonged or repeated contact is likely.

Inhalation: None required; however, use of adequate ventilation is good industrial practice.

Respiratory Protection: None required.

Other Protective Equipment: None required.

10.0 STABILITY AND REACTIVITY

Stability: Stable

Viscosity SUS @ 100°F: Greater than or = to 100

Conditions to Avoid: None identified

Materials to Avoid: Avoid strong oxidizers such as hydrogen peroxide, bromine and chromic acid.

Hazardous Decomposition: Carbon monoxide and carbon dioxide from burning; oxides of sulfur; oxides of nitrogen; sulfur dioxide or hydrogen sulfide, depending upon decomposition conditions; oxides of calcium.

11.0 TRANSPORTATION INFORMATION

U.S. Department of Transportation

Shipping Name: Not Regulated **Reportable Quantity:** N/A

Freight Classification: Petroleum Lubricating Grease

Special Transportation Notes: N/A

12.0 ENVIRONMENTAL /SAFETY REGULATIONS

Section 313 (Title III Superfund Amendment and Reauthorization Act): This product does not contain any chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Last Revision: 4/1/96

This material safety data sheet conforms to the requirements of ANSI Z400.1.

This material safety data sheet and the information it contains is offered to you in good faith as accurate. It may not be valid for this material if used in combination with any other material or in any other process. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his or her own particular use. Chem and Lube assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.